

# Air-Pro

Blue Polyethylene (PE)  
Compressed Air Piping System  
REV:IN0512PE



---

VALVES • ACTUATORS • HIGH PURITY PIPING • INDUSTRIAL PIPING • ENVIRONMENTAL PIPING • WET PROCESS SOLUTIONS

---

Material ASTM D3350 cell classification PE445574E or better. Resin shall comply with FDA Code of Federal Regulators (CFR), Title 21, Chapter 1: Section 177.1520 determining suitability for contact with foodstuff.

Meets Cal/OSHA requirements for transport of compressed air

Pipe Production Dimensions and tolerances shall exceed ISO 15494 requirement.

Fitting Production Dimensions and tolerances shall exceed ISO 15494 requirement.

Pressure Rating Components shall be pressure rated in accordance with ASTM D2837 and DIN 8077 for hydrostatic design basis. Components shall be manufactured to standard dimensional ratio (SDR) 7 & 11.

Based on continuous service life of 50 years at 68F (20C).  
SDR7: 230psi (PN16)  
SDR11: 150psi (PN10)  
PN = Nominal pressure in bar.

Joining Available methods shall be according to the schedule below  
DVS 2208-1 Socket: 1/2" (20mm) through 4" (110mm)  
DVS 2207-1 Contact Butt: 1/2" (20mm) through max product size

**The  
Wet  
Process  
People™**

**Another  
Corrosion  
Problem  
Solved.™**

---

655 Andover St. Lawrence, MA 01843 – [www.asahi-america.com](http://www.asahi-america.com) – [asahi@asahi-america.com](mailto:asahi@asahi-america.com) - 800-343-3618